

SOLYX SimGlas®

SGC-02 Gold Weave



Product Details

SGC-6521-58 Ice Melt is a lightly textured film made from durable polyester that provides a distracted view. This dimensionally stable film is 100% UV stabilized, will not discolor nor shrink, and is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive. It is recommended for application to interior glass and is ideal for semi-private distraction in decorative or architectural applications.

Flammability Rating

The product meets ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same methods used for installing window tinting films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SGC-02 Gold Weave consists of an elegant weave design highlighted with a metallic gold finish and lightly textured surface. When viewed from the adhesive side, the metallic color is silver.

Specifications

| | |
|----------------------------|----------------------|
| Product Code | SGC-02 |
| Product Family | Geometric/Rectangles |
| Film Type | Polyester |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior |
| Available Width(s) | 59" |
| Full Roll Length | 100 linear feet |
| Thickness | 2 mil |
| Visible Light Transmission | 48% |
| UV Rejection | 99% |
| Solar IR Energy Rejected | 56% |

Product Construction

Face Film

2 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Transparent Synthetic