

## SOLYX SimGlas®

### SGC-6515 Fluted Glass



#### Product Details

**SGC-6515 Fluted Glass** is an adhesive polyester film that nicely simulates textured glass with vertical, crystal clear fluted lines that provide semi-private distortion. The flutes are 3/16" wide with 0.1875" spacing between. This dimensionally stable film is 100% UV stabilized, will not discolor nor shrink, and is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive. It is recommended for application to interior glass and is ideal for semi-private distraction in decorative or architectural applications.

#### Flammability Rating

The product meets ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Product Description

**SGC-6515 Fluted Glass** is a textured, transparent polyester film that provides a softened, distorted view and excellent light transmission.

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same methods used for installing window tinting films.

##### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC  
1-888-657-5224  
[www.decorativefilm.com](http://www.decorativefilm.com)

#### Specifications

Product Code	SGC-6515
Product Family	Organic
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	58"
Full Roll Length	50 linear feet
Thickness	2 mil
Shading Coefficient	.93
Visible Light Reflectance	7%
Visible Light Transmission	90%
UV Transmission	1%
Solar Energy Absorbed	28%
Solar IR Energy Rejected	15%

#### Product Construction

##### Face Film

2 mil Polyester

##### Adhesive

Clear, Pressure-Sensitive

##### Release Liner

Transparent Synthetic