

SOLYX® Glass Finishes

SimGlas® SGV-6614 Fleur De Lis



Product Details

SimGlas® SGV-6614 Fleur De Lis is a durable, frosty, polymeric PVC film with a semi-clear 1-1/2" x 2" fleur-de-lis (lily flower) pattern. This UV stabilized film, which will not discolor nor shrink, is manufactured with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive. It is recommended for application to interior and exterior glass (inside surface) including skylights (inside surface), and is perfect for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same methods used for installing window tinting films.

Warranty

This **SimGlas®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SimGlas® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SimGlas® SGV-6614 Fleur De Lis is a durable, frosty, polymeric film with a semi-clear 1-1/2" x 2" classic fleur-de-lis pattern. This film obscures visibility while allowing excellent light transmission.

Specifications

Product Code	SGV-6614
Product Family	Geometric
Film Type	Vinyl
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	48"
Full Roll Length	50 linear feet
Thickness	5 mil
Visible Light Reflectance	7%
Visible Light Transmission	83%
UV Transmission	39%
Solar Heat Reflectance	7%
Solar Heat Transmission	76%

Product Construction

Face Film

5 mil Polymeric Vinyl

Adhesive

Clear, Pressure-Sensitive

Release Liner

Transparent Synthetic