Specification Sheet

SOLYX_® Glass Finishes SX-1002 Clear Sand Blast



Product Description

SOLYX® **SX-1002 Clear Sand Blast** is a translucent, embossed vinyl film made to replicate the look of sand blasted glass. This product is ideal for obscuring direct visibility while allowing excellent light transmission.

Specifications

| ••••••••••••••••••••••••••••••••••••••• | |
|---|-------------------------|
| Product Code | SX-1002 |
| Product Family | Frosted |
| Film Type | Polymeric Vinyl |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior or Exterior |
| Available Width(s) | 12", 24", 36", 48", 60" |
| Full Roll Length | 100 linear feet (30.5m) |
| Thickness | 6 mil |
| Shading Coefficient | .93 |
| Visible Light Reflection | 70% |
| Visible Light Transmission | 53% |
| UV Transmission | 22% |
| Solar Heat Reflection | 7% |
| Solar Heat Transmission | 76% |
| Infra-Red Transmission | 50% |
| | |

Product Construction

Face Film 5 mil PVC

Adhesive

Clear, Pressure-Sensitive, 0.7 - 0.87 mil

Release Liner Silicone Coated

Product Details

SOLYX® SX-1002 Clear Sand Blast is a durable, embossed vinyl film made to replicate the look of sand blasted glass. Supplied with a silicone coated liner and pressure-sensitive adhesive, it is recommended for application to interior glass and exterior glass and is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code[®].

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com