

Solyx® SX-1103-UG

Printable Clear Polyester Film



A versatile, high-quality printable film that brings your customer's designs to life.

Product Description

SX-1103-UG is a highly printable, optically clear polyester film. The non-SR surface makes it a versatile solution for UV, Solvent, and latex printing methods, featuring a 4 mil liner for functional plotting applications.

Construction

Face Film

2 mil, PVC-Free Polyester

Adhesive

Clear, Removable

Release Liner

4 mil, Clear Polyester

Key Features

- **UltraGreen®** is a sustainable product collection that is Eco-Friendly & Intertek® Clean Air Gold Standard Certified



- **Clarity:** Optically Clear



- **Print Method:** UV, Solvent, and Latex Printable



- **Adhesive:** High Peel, Removable



- **Liner:** Plottable, Clear PET



- **Lamination:** Can be used for temporary application on exterior surfaces



- **Available Width:** 60 inches



Solyx[®] SX-1103-UG

Printable Clear Polyester Film



Specifications

Product Family	Print and Plot
Film Type	PVC-Free Polyester
Adhesive Type	Acrylic, Removable
Usage	Interior / Temporary Exterior
Available With(s)	60 inches
Full Roll Length	157 Linear Feet
Thickness	2 mil

LET'S STAY IN TOUCH



John Sharkey 
Director of Sales
jsharkey@decorativefilm.com
Cell: 610-246-7621



Register your wholesale account using this QR code



SOLYX®

SX-1103-UG Printable Clear Polyester

Product Details

SOLYX® SX-1103-UG Printable Clear Polyester is a polyester film with a highly printable topcoat. The pressure-sensitive adhesive is protected by a synthetic polyester liner.

Specifications

Product Code	SX-1103-UG
Product Family	Print Media
Film Type	Polyester
Adhesive Type	Acrylic, Removable
Usage	Interior / Temp. exterior
Available Width	60"
Full Roll Length	157 Linear Feet
Thickness	2 mil
IR Transmission	92%
Visible Light Transmission	91%
UV Transmission	84%
Shelf Life	2 years

Product Construction

Face Film

2 mil Polyester

Adhesive

Removable acrylic, Pressure-Sensitive

Release Liner

4 mil, Synthetic Polyester

Printing and graphic plotting*

This printable film is provided for general use, but its suitability for specific applications may vary. Users are advised to conduct thorough testing with their equipment and under their specific conditions to determine its compatibility and performance for their intended purposes. The manufacturer makes no guarantees, expressed or implied, regarding the fitness of this film for any particular printing application. Usage without prior testing is at the user's discretion and risk. It is the responsibility of the user to ensure that the film meets their specific requirements before full-scale production or critical applications. For most masking applications, R-Tape 4075RLA is recommended.

Product Description

SOLYX® SX-1103-UG Printable Clear Polyester is an optically clear polyester film with a printable* surface compatible with UV, Solvent, or Latex ink printers. The 4mil silicone-coated liner is suitable for computer graphic cutting and protects the pressure-sensitive adhesive. It is recommended for application to interior and temporary exterior facing glass.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films. Installers should work with clean hands when handling this film.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years interior from the date of installation. See warranty information for specific details. The warranty does not apply to film problems caused by defective application.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com