

SOLYX® Glass Finishes SX-1109 Cut Glass Neptune



Product Details

SOLYX® SX-1109 Cut Glass Neptune is a beautiful, translucent, embossed film with a textured facet design that scatters light and creates a distorted view. Made of durable polypropylene with a clear, removable release liner, it has a total nominal thickness of between 7 and 9 mils. This film is recommended for application to interior and exterior glass (inside surface) as well as plastics and polycarbonate sheets. It is an excellent privacy film and is ideal for decorative or architectural applications.

Note: This film is also available in a static cling version, SX-SC109 Neptune.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SX-1109 Cut Glass Neptune is a beautiful, embossed film with a textured facet design that scatters light and creates a distorted view while allowing excellent light transmission.

Specifications

Product Code	SX-1109
Product Family	Geometric
Film Type	Polypropylene
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	48"
Thickness	+/-8 mil
IR Transmission	51%
Visible Light Transmission	69%
UV Transmission	24%
Absorption	45%
Total Solar Energy Rejected	56%

Product Construction

Face Film

8 mil Polypropylene

Adhesive

Pressure-Sensitive Adhesive

Release Liner

Transparent Synthetic