

## SOLYX SimGlas®

### SX-1257 6-Inch Glass Block



#### Product Details

**SX-1257 6-Inch Glass Block** is a lightly textured, semi-transparent film made from durable polyester that closely resembles 6" real glass blocks. This timeless pattern of wavy glass provides a distorted privacy view, is dimensionally stable and 100% UV stabilized, and will not discolor nor shrink. Supplied with a silicone coated removable liner which protects the clear, pressure-sensitive acrylic adhesive, it is recommended for application to interior glass. This film is ideal for privacy distraction in decorative or architectural applications.

#### Flammability Rating

The product meets ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Product Description

**SX-1257 6-Inch Glass Block** is a lightly textured, semi-transparent, polyester film that simulates glass blocks and provides a distorted view with excellent light transmission.

#### Specifications

|                            |                    |
|----------------------------|--------------------|
| Product Code               | SX-1257            |
| Product Family             | Geometric          |
| Film Type                  | Polyester          |
| Adhesive Type              | Pressure-Sensitive |
| Usage                      | Interior           |
| Available Width(s)         | 54"                |
| Full Roll Length           | 90 linear feet     |
| Thickness                  | 2 mil              |
| Shading Coefficient        | .93                |
| Visible Light Reflectance  | 7%                 |
| Visible Light Transmission | 90%                |
| UV Transmission            | 1%                 |
| Solar Energy Absorbed      | 28%                |
| Solar IR Energy Rejected   | 15%                |

#### Product Construction

##### Face Film

2 mil Polyester

##### Adhesive

Clear, Pressure-Sensitive

##### Release Liner

Transparent Synthetic

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same methods used for installing window tinting films.

##### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)