

## SOLYX® Glass Finishes

### SX-1950 Anti-Graffiti



#### Product Description

SOLYX® SX-1950 Anti-Graffiti protective film is a durable, optically clear, scratch resistant, removable product that acts as a sacrificial barrier between vandals and the surfaces they cover, including exterior glass windows and mirrors as well as other non-porous surfaces like stainless steel and marble.

#### Specifications

Product Code	SX-1950
Product Family	Specialized Function
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Exterior
Available Width(s)	60", 72"
Full Roll Length	100 linear feet (31.5)
Thickness	4 mil
Tensile Strength	30,000 lbs/sq in
Shading Coefficient	1.11
Visible Light Reflectance	9%
Visible Light Transmittance	93%
UV Transmittance	<1%
Solar Heat Reflectance	8%
Solar Heat Transmittance	80%
Total Solar Energy Rejected	16%

#### Product Construction

##### Face Film

4 mil Clear Polyester

##### Adhesive

Clear, Pressure-Sensitive, Removable

##### Release Liner

Silicone Coated Polyester

#### Product Details

SOLYX® SX-1950 Anti-Graffiti protective film is a durable, optically clear, scratch resistant, and removable product that acts as a sacrificial barrier between vandals and the surfaces they cover, including exterior glass windows and mirrors as well as other non-porous surfaces like stainless steel and marble. This unnoticeable film protects surfaces from paint, key scratches, marking, and even acid-etching. When vandalized, the film is easily removed and replaced, reducing property damage and maintaining aesthetics.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of three (3) years from the date installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)