

SOLYX® Glass Finishes

SX-2011 Micro Dot



Product Description

 ${f SOLYX} {f @}$ **SX-2011 Micro Dot** is a clear polyester film with a pattern of tiny 1/16" white hexagons that creates a screen effect. It is ideal for obscuring visibility while allowing excellent light transmission.

Specifications

| Product Code | SX-2011 |
|----------------------------|-------------------------|
| Product Family | Patterned Privacy |
| Film Type | Polyester |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior or Exterior |
| Available Width(s) | 60" |
| Full Roll Length | 100 linear feet (30.5m) |
| Thickness | 2 mil |
| Shading Coefficient | 0.82 |
| Visible Light Reflection | 22% |
| Visible Light Transmission | 43% |
| UV Transmission | 27% |
| Solar Heat Reflection | 18% |
| Solar Energy Absorbed | 22% |
| Glare Reduction | 28% |
| Infra-Red Transmission | 56% |
| U Value | 1.09 |
| Emissivity | 0.85 |
| | |

Product Construction

Face Film

2 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Product Details

SOLYX® **SX-2011 Micro Dot** is a clear polyester film with a pattern of tiny 1/16" white hexagons that creates a screen effect. Manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive, it is designed for application to interior glass, single- or double-pane, and exterior-facing glass, and can also be installed on exterior applications. This film is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & SealantsThis product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

 $SOLYX @ \ \ Decorative \ Films \ are \ available \ through \ authorized \\ Installing \ Dealers, \ Distributors, \ or \ directly \ from \ Decorative \ Films, \ LLC.$

Samples submitted upon request.

Contact Information

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com