

SOLYX®

SX-2300 Printable Clear Polyester SR

Product Details

SOLYX® SX-2300 Printable Clear Polyester SR is a polyester film with a printable scratch-resistant topcoat. The acrylic pressure-sensitive adhesive is protected by a synthetic polyester liner.

Specifications

Product Code	SX-2300
Product Family	Print Media
Film Type	Polyester
Adhesive Type	Clear, removable
Usage	Interior
Available Width(s)	60" and 72"
Full Roll Length	215 linear feet
Thickness	2 mil
Infrared Transmission	93%
Visible Light Transmission	92%
UV Transmission	<1%
Shelf Life	2 years

Product Construction

Face Film

2 mil Polyester, SR Coating

Adhesive

Removable acrylic, Pressure-Sensitive

Release Liner

3 mil, Synthetic Polyester

Printing and graphic plotting*

This UV printable film is provided for general use, but its suitability for specific applications may vary. Users are advised to conduct thorough testing with their equipment and under their specific conditions to determine its compatibility and performance for their intended purposes. The manufacturer makes no guarantees, expressed or implied, regarding the fitness of this film for any particular printing application. Usage without prior testing is at the user's discretion and risk. It is the responsibility of the user to ensure that the film meets their specific requirements before full-scale production or critical applications. For most masking applications, R-Tape 4075RLA is recommended.

Product Description

SOLYX® SX-2300 Printable Clear Polyester SR is a durable polyester film with a UV printable* and scratch-resistant topcoat. The 3mil silicone-coated liner is suitable for computer graphic cutting and protects the pressure-sensitive adhesive. It is recommended for application to interior and exterior facing glass.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films. This film does take on fingerprints but is fully washable and cleans easily with SimGlas Window Film Cleaner and Polish. Installers should work with clean hands when handling this film.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years interior from the date of installation and (1) year for exterior applications. Life expectancy is 3-5 years for exterior applications. See warranty information for specific details. The warranty does not apply to film problems caused by defective application.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224

www.decorativefilm.com