

SOLYX® Graphic Media SX-2776 White Printable Wall Canvas



Product Description

SOLYX® SX-2776 White Printable Wall Canvas is a white opaque film made of woven polyester and microsphere adhesive for dry installation.

Specifications

| | |
|-----------------------------|-----------------|
| Product Code | SX-2776 |
| Product Family | Graphic Media |
| Film Type | Woven Polyester |
| Adhesive Type | Microsphere |
| Usage | Interior |
| Available Width(s) | 60" |
| Full Roll Length | 100 linear feet |
| Thickness | 12 mil |
| Visible Light Transmittance | <1% |

Product Construction

Face Film

12 mil Woven Polyester

Adhesive

Repositionable Microsphere

Release Liner

90# Stayflat Paper Liner

Product Details

Intended for use on high quality interior wall marking or decal applications requiring durability, flexibility, and low shrinkage and edge curl, such as wall decorations and point of purchase decals.

Features

- Repositionable
- Dry Install - no adhesives paste required
- Can be digitally printed – Solven, Latex, UV cured inks
- Installs over any stable smooth surface with Level 5 finish
- Application temperature to be +50 degree Fahrenheit with 50% relative humidity

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for dry application films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com

Installation guidelines for SX-2776 White Printable Wall Canvas.

APPLICATION ENVIRONMENT - Product is intended for interior use only.

APPLICATION SURFACE - Flat, smooth painted (non-vinyl) wallboards

Please note: A semi-gloss painted surface provides the best adhesion. Flat paint or textured finish can be problematic along with any anti-graffiti coatings.

WALL INSPECTION AND REPAIR - This information is intended as guidance only. We recommend that all surfaces be tested for compatibility and removability. Factors such as the smoothness and cleanliness of the surface, as well as print, process, installation method, and size of the decal may impact the adhesion and success of the application.

- This product is designed to adhere to clean, smooth painted wallboards.
- A 50/50 mixture of water and alcohol should be used to clean the wall surface prior to installation. Let surface full dry.
- Bubbles, cracks, or any other imperfections must be repaired before application. If repair requires the use of spackle, it should be primed over and painted, and allowed to cure.
- If the wall is freshly painted, please refer to the paint manufacturer's statement regarding dry time.
- If the wall surface needs cleaning only, clean with soapy water and isopropyl alcohol and dry with a lint-free towel.
- Apply a small swatch of the film to the prepared wall surface in an inconspicuous area and allow the swatch to dwell for 72 hours. Slowly remove the film at a 45–90-degree angle and inspect for possible damage to the wall. If any paint is removed, re-inspect the wall surface for cure of the paint to the wallboard.

INSTALLATION - *Please note: the below information provides basic information on installation. Professional installers can be hired to ensure proper application of finished graphics.*

- Use of premask is not recommended.
- Film should be removed from its packaging, allowed to lay flat and acclimate to the room environment prior to installation.
- The minimum temperature is 50F (10C) with 50% relative humidity.
- Avoid applying to an area directly near a heater or source of condensation.
- Make sure your film is centered properly.
- Dry application. No wetting agent is recommended for application to wallboard or other wall coverings. Condensation left behind the film will cause the film to lift.
- Bend back approximately two inches of the release liner from the top portion of the film.
- Be careful not to stretch the film as films have memory and when stretched, will ultimately relax, causing lifting and failure.
- Using a felt-tipped squeegee, lightly squeegee the center top of the exposed adhesive area of the film, working the middle section of the film first. Use firm, even strokes as you work your way from the center to either side. Continue to slowly remove the paper liner while squeegeeing horizontally with overlapping strokes, working from top to bottom and from center to sides. Be sure to squeegee the entire film surface to ensure adequate adhesion.
- Overlapping seams with "double-cut", if necessary, are recommended for full wall installation.