

SOLYX® Glass Finishes

SX-3065 Spectrum Transparent Dichroic Film - With Adhesive and Scratch Resistant Surface



Product Details

SOLYX® SX-3065 Spectrum Transparent Dichroic Film – With Adhesive and Scratch Resistant Surface is a reflective, metal-free film made of durable, multi-layered polyester for color shifting special effects. Manufactured with a scratch resistant coating and a silicone coated liner which protects the clear, pressure-sensitive adhesive, it is designed for application to interior glass surfaces. This transparent film is ideal for decorative or architectural applications.

ALSO AVAILABLE:

SX-3050 Spectrum with NO adhesive – 40” wide

SX-SC306 Spectrum with static cling adhesion – 59” wide

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com

Product Description

SOLYX® SX-3065 Spectrum Transparent Dichroic Film – With Adhesive and Scratch Resistant Surface is a reflective, metal-free film made of multi-layered polyester for color shifting special effects.

Specifications

Product Code	SX-3065
Product Family	Specialized Function
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	60”
Full Roll Length	100 linear feet (30.5m)
Thickness	1.5 mil
Colors	Cyan/Blue/Magenta
Visible Light Reflection	15%
Visible Light Transmission	78%
UV Transmission	37%
Total Solar Energy Rejected	45%
Solar Energy Absorbed	22%
Glare Reduction	35%

Product Construction

Face Film

1.5 mil Polyester

Adhesive

.5 mil Clear, Pressure-Sensitive

Release Liner

Silicone Coated