

SOLYX® Glass Finishes

SX-3131 Eco Dusted



Product Details

SOLYX® SX-3131 Eco Dusted is a durable polyester film with a scratch resistant, dusted matte finish that matches dusted crystal films. Supplied with a low-gloss surface that eliminates glare, a heavy silicone coated liner suitable for computer graphic cutting, and a pressure-sensitive adhesive, it is recommended for application to interior and exterior facing glass. This film is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Product Description

SOLYX® SX-3131 Eco Dusted is a polyester film with a scratch resistant, dusted matte finish that matches dusted crystal films. This product is ideal for obscuring direct visibility while allowing excellent light transmission.

Specifications

| | |
|----------------------------|-------------------------|
| Product Code | SX-3131 |
| Product Family | Frosted |
| Film Type | Polyester |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior |
| Available Width(s) | 60" |
| Full Roll Length | 100 linear feet (30.5m) |
| Thickness | 3 mil |
| Shading Coefficient | .93 |
| Visible Light Reflection | 69% |
| Visible Light Transmission | 59% |
| UV Transmission | 45% |
| Solar Heat Reflection | 68% |
| Solar Heat Transmission | 32% |
| Infra-Red Transmission | 66% |

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films. This film does take on fingerprints but is fully washable and cleans easily with SimGlas Window Film Cleaner and Polish. Installers should work with clean hands when handling this film.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details. The warranty does not apply to film problems caused by defective application.

Product Construction

Face Film

3 mil Polyester, SR Coating

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated, Plottable

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com