

SOLYX® Glass Finishes

SX-3138 Milky Whiteout



Product Details

SOLYX® SX-3138 Milky Whiteout is an opaque, white polyester film with a gloss finish. This durable film is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive, and is designed for application to interior glass, single-or double-pane, exterior facing glass, and exterior glass. Safe for use on all types of glass without the fear of thermal shock glass breakage, this film is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SX-3138 Milky Whiteout is an opaque, white polyester film with a gloss finish. It is ideal for obscuring direct visibility while allowing some light transmission.

Specifications

Product Code	SX-3138
Product Family	Design-Free
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior or Exterior
Available Width(s)	36", 72"
Full Roll Length	100 linear feet (30.5m)
Thickness	2 mil
Visible Light Transmission	3.6%
UV Rejection	100%
Infrared Rejection	75%

Product Construction

Face Film
2 mil Polyester

Adhesive
Clear, Pressure-Sensitive

Release Liner
Silicone Coated