

SOLYX® SX-4081-UG Alphabet Frosted



Specifications

Product Code	SX-4081-UG
Product Family	Themes
Film Type	Polyester
Adhesive Type	Adhesive
Usage	Interior
Available Width(s)	48"
Full Roll Length	100 linear feet
Thickness	3 mil
Visible Light Transmission	59%
UV Rejection	45%
Infra-Red Transmission	66%

Product Construction

Face Film

3 mil Polyester

Adhesive

Removable, Pressure-Sensitive

Release Liner

Silicone Coated

Product Description

SX-4081-UG Alphabet Frosted is perfect for kids' rooms, doctors' offices, and classrooms.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. The film is applied using the same tools and techniques used for installing window tinting films but can also be applied dry when using much care. Installers should work with clean hands when handling this film.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation on interior applications. See warranty information for specific details. The warranty does not apply to film problems caused by defective application.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com