

SOLYX® Glass Finishes

SX-5033 Matte Spring Buds



Product Details

SOLYX® SX-5033 Matte Spring Buds is a durable polyester film with a pattern of budding white branches on a translucent matte background. It is supplied with a silicone coated liner, which protects the clear, pressure-sensitive adhesive and is recommended for application to interior, single- or double-pane, and exterior glass. It is perfect for semi-privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Product Description

SOLYX® SX-5033 Matte Spring Buds is a beautiful silhouette pattern of budding white branches on a translucent matte background. It effectively obscures visibility while allowing good light transmission.

Specifications

Product Code	SX-5033	
Product Family	Organic	
Film Type	Polyester	
Adhesive Type	Pressure-Sensitive	
Usage	Interior and Exterior	
Available Width(s)	60" (1524mm)	
Full Roll Length	100 linear feet	
Thickness	2 mil	
Visible Light Transmission	35%	ASTM D 1003
UV Transmission	17%	
Infra-Red Transmission	31%	
Tensile strength	MD: 18 Kg/mm ²	ASTM D 882
	TD: 23 Kg/mm ²	
Elongation	MD: 140 %	ASTM D 882
At Break	TD: 105 %	
Friction	0.25 uk	ASTM D 1894
Coefficient	0.41 us	ASTM D 1894
Surface roughness	0.220 um	
Haze	60%	ASTM D 1003
Gloss	37%	ASTM D 523
Heat Shrinkage	MD: 2.9 %	150 Degree C – 30min
	TD: 0.3 %	

Product Construction

Face Film

2 mil Polyester

Adhesive

0.8 to 1.0 mil, Clear, Acrylic, Pressure-Sensitive

Release Liner

2 mil Polypropylene, Silicone Coated (Thickness variation +/- 10%)

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of interior installation. Exterior installations have a three (3) year warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com