


## SOLYX® Glass Finishes

### SX-5034 Matte Sugari



#### Product Description

SOLYX® SX-5034 Matte Sugari is a polyester film with white fiberglass mesh circles on a translucent matte background. This film effectively obscures visibility while allowing good light transmission.

#### Specifications

Product Code	SX-5034	
Product Family	Organic	
Film Type	Polyester	
Adhesive Type	Pressure-Sensitive	
Usage	Interior and Exterior	
Available Width(s)	60" (1524mm)	
Full Roll Length	100 linear feet	
Thickness	2 mil	
Visible Light Transmission	41%	ASTM D 1003
UV Transmission	20%	
Infra-Red Transmission	50%	
Tensile strength	MD: 18 Kg/mm <sup>2</sup> TD: 23 Kg/mm <sup>2</sup>	ASTM D 882
Elongation	MD: 140 %	ASTM D 882
At Break	TD: 105 %	
Friction	0.25 uk	ASTM D 1894
Coefficient	0.41 us	ASTM D 1894
Surface roughness	0.220 um	
Haze	60%	ASTM D 1003
Gloss	37%	ASTM D 523
Heat Shrinkage	MD: 2.9 % 150 Degree C – 30min TD: 0.3 %	

#### Product Construction

##### Face Film

2 mil Polyester

##### Adhesive

0.8 to 1.0 mil, Clear, Acrylic, Pressure-Sensitive

##### Release Liner

1 mil Polyester, Silicone Coated (Thickness variation +/- 10%)

#### Product Details

SOLYX® SX-5034 Matte Sugari is a durable polyester film with white fiberglass mesh circles on a translucent matte background. The circles range in size from approximately 1-1/2" to 2". It is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive, and is recommended for application to interior, single- or double-pane, and exterior glass. It is ideal for semi-privacy, decorative, or architectural applications.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of interior installation. Exterior installations have a three (3) year warranty. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)