



# SX-8783-UG Eco Sand Blast



# **Product Description**

SOLYX® SX-8783-UG Eco Sand Blast

Introducing **UltraGreen**, an innovative collection of decorative privacy window films utilizing advanced, VOC-free coating technology and eco-friendly PVC-free materials to create an environmentally responsible product with exceptional performance.

# **Specifications**

Product Code	SX-8783-UG
Product Family	Frosted & Design Free
Film Type	Polycarbonate
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	54"
Full Roll Length	100 linear feet
Thickness	3 mil
Visible Light Transmission	54%
UV Transmission	23%
Infra-Red Transmission	48%

# **Product Construction**

### **Face Film**

3 mil Polycarbonate

### **Adhesive**

Permanent, Pressure-Sensitive

# **Release Liner**

3 Mil Liner

## **Product Details**

SOLYX® SX-8783-UG Eco Sand Blast is a translucent, lightly textured film made from durable, dimensionally stable polycarbonate. Manufactured with a silicone coated liner which protects the clear pressure-sensitive adhesive, it is recommended for application to glass, acrylic and polycarbonate sheeting. This film is ideal for privacy, decorative or architectural applications.

### **Flammability Rating**

Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0 UL 94 Rating UL 94 UL Classification V-O Class A 0 -25 Flame Spread Index 0 -450 Smoke Developed Index

#### Features

Service Temperature Range -40°F to +225°F Adhesive Thickness – 1.3-1.7 mils Shelf Life (@ 73°F, 50% RH) 2 years Static Shear (1" x 1" x 1000 grams) >200 hours Outdoor Life of Film 5 years. Indoor 10 years UV Block 100% 200 nm – 360 nm 98% 360 nm – 400 nm

### **Chemical Resistance**

Distilled Water (24 hr) No Effect
Detergent (24 hr) No Effect
10% HC1 (10 min) No Effect
10% Ammonium Hydroxide (10 min) No Effect
Gasoline (1 hr) No Effect

# Installation and Warranty

### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

## Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

# **Product Distribution and Contact Information**

### Distribution

 ${\bf SOLYX} \& \ \ {\bf Decorative\ Films\ are\ available\ through\ authorized} \\ Installing\ Dealers,\ Distributors,\ or\ directly\ from\ Decorative\ Films,\ LLC. \\ Samples\ submitted\ upon\ request.$ 

## **Contact Information**

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com

Country of Origin: Made in the USA