

SOLYX® Glass Finishes SX-BSFAC-02 Frost Bird Safety Film



Product Details

SOLYX® SX-BSFAC-02 Frost Bird Safety Film is a durable, UV stabilized, optically clear, outside weatherable, scratch resistant film with a specially designed frosted bird pattern on clear film made to break reflections on the glass allowing birds to see that there is an obstruction. The artwork depicts blooming mountain laurel surrounding six bird species native to southwestern Pennsylvania. Made with 4mil heavy-duty polyester bonded by strong adhesives, this film provides a clear yet powerful barrier that helps hold glass in place in the event of an impact or earthquake. It is recommended for application to **exterior glass ONLY**.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of three (3) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SX-BSFAC-02 Frost Bird Safety Film is a durable polyester film with a pattern of frosted birds among blooming mountain laurel that deters birds from flying into reflective glass.

Specifications

Product Code	SX-BSFAC-02
Product Family	Specialized Function
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	EXTERIOR ONLY
Available Width(s)	48"
Full Roll Length	98 linear feet
Thickness	4mil
Shading Coefficient	.93
Visible Light Reflectance	10%
Visible Light Transmission	89%
UV Transmission	<1%
Solar Heat Reflectance	8%
Solar Heat Transmission	78%
Solar Heat Absorbance	14%

Product Construction

Face Film

4mil Polyester

Adhesive

Adhesive Clear, Pressure-Sensitive

Release Liner

Transparent, Synthetic