

SOLYX® Glass Finishes SX-C300 Dusted Etch



PRODUCT DETAILS

SOLYX® SX-SC300 Dusted Etch is a solid grey color with a matte etched finish. This product is ideal for obscuring direct visibility while allowing excellent light transmission. This film has a polyester silicone liner and pressure-sensitive adhesive. It is perfect for privacy, decorative or architectural applications and installed with the same tools and methods as are window films. (Note: This film is transparent when wet)

Fire Rating

When applied to glass or plastic surfaces:
Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
UL 94 Rating UL Classification V-O
Class A 0 -25 Flame Spread Index 0 -450

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24)

Product Description

SOLYX® SX-SC300 Dusted Etch is a solid color, etched finish, polyester film. This product is ideal for obscuring direct visibility while allowing excellent light transmission.

Specifications

Product Code	SX-C300
Product Family	Plain Frosted
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	60"
Full Roll Length	100 linear feet
Thickness	2 mil

Visible Light Transmission	30%
UV Transmission	24%
Solar Heat Transmission	7%
Infra-Red Transmission	76%

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details. 15 year expected life for interior applications

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Construction

Face Film

2 mil polyester

Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

Release Liner

1.5 mil Silicone