

SOLYX® Glass Finishes SX-C371 Structure



SOLYX: SX-C371
Structure

PRODUCT DETAILS

SOLYX® **SX-SC371 Structure** is a textured white patterned film with a clear background. A high grade polyester film this product is ideal for semi-obscuring direct visibility while allowing excellent light transmission.. This film has a silicone liner and pressure-sensitive adhesive.

Fire Rating

When applied to glass or plastic surfaces:
Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
UL 94 Rating UL Classification V-O
Class A 0 -25 Flame Spread Index 0 -450

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24)

Product Description

SOLYX® **SX-SC371 Structure** is a textured white patterned film with a clear background. A high grade polyester film this product is ideal for semi-obscuring direct visibility while allowing excellent light transmission.

Specifications

Product Code	SX-C371
Product Family	Arch/Stripes and patterns
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	48" (1220mm)
Full Roll Length	50 linear feet
Thickness	2 mil
Shading Coefficient	.93%
Visible Light Reflection	70%
Visible Light Transmission	30%
UV Transmission	24%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	39%

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® **Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Construction

Face Film

2 mil polyester

Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

Release Liner

1.5 mil Silicone