

SOLYX® Glass Finishes

SX-C391 Swiss



Product Details

SOLYX® SX-C391 Swiss is a white matte film with a diagonally arranged pattern of 3/32" clear dots with 1/4" spacing. Made of durable polyester, it is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive. This film is recommended for application to interior glass and is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Product Description

SOLYX® SX-C391 Swiss is a durable white matte film with a diagonally arranged pattern of 3/32" clear dots with 1/4" spacing. This film provides obscured visibility and excellent light transmission.

Specifications

Product Code	SX-C391
Product Family	Geometric
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	60"
Full Roll Length	100 linear feet
Thickness	2 mil
Shading Coefficient	.93
Visible Light Reflectance	70%
Visible Light Transmission	53%
UV Transmission	5%
Solar Heat Reflectance	7%
Solar Heat Transmission	76%
Infra-Red Transmission	21%

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Construction

Face Film

2 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

1.5 mil Silicone Coated