Specification Sheet



SOLYX. SX-SC155 Crystal Lattice



Product Description

SOLYX SX-SC155: Crystal Lattice

A fully removable and reusable film ideal for obscuring daytime view and providing excellent shading with good light transmission.

Specifications

Product Code	SX-SC155
Product Family	Elegant Textured
Film Type	Polypropylene
Adhesive Type	Non Adhesive Static Cling
Usage	Interior or Exterior
Available Width(s)	36"
Thickness	9 mil
IR Transmission	75%
Visible Light Transmission (%)	65%
UV Transmission (%)	1%

Product Construction

Face Film: 9mil Polypropylene Non-Adhesive: Static Cling Liner: Transparent Synthetic

Product Detail

SOLYX® <u>SX-SC155: CRYSTAL LATTICE</u> Film is recommended for application to interior glass and exterior glass (inside surface) or plastics and polycarbonate sheets. This film is made of durable Static Cling polypropylene film with an embossed textured surface and clear removable release liner.

** Image product code should be SX-SC155

Fire Rating

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code[®].

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions. Installed using the same methods for installing window films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See Warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC

Samples submitted upon request.

Contact Information

Contact Decorative Films, LLC at 1-888-657-5224 or www.decorativefilm.com