

SOLYX® Glass Finishes

SX3-314 Acid Etch



Product Description

SOLYX® SX3-314 Acid Etch is a vinyl film with a matte finish that simulates soft, frosted, acid-etched glass. This film is more transparent than dusted crystal films and is ideal for semi-obscuring direct visibility while allowing excellent light transmission.

Specifications

Product Code	SX3-314
Product Family	Frosted
Film Type	Vinyl
Adhesive Type	Pressure-Sensitive
Usage	Interior or Exterior
Available Width(s)	54", 60"
Full Roll Length	150 ft
Thickness	3 mil
Visible Light Transmission	78%
UV Transmission	22%
Infra-Red Transmission	79%

Product Construction

Face Film

3 mil Vinyl

Adhesive

Water-Based Acrylic, Clear, Pressure-Sensitive (Note: Adhesive will whiten when installed with water solution and clears once cured.)

Release Liner

Paper on all widths

Product Details

SOLYX® SX3-314 Acid Etch is a durable vinyl film with a matte, low-gloss finish that eliminates glare and simulates soft, frosted, acid-etched glass. Supplied with a paper release liner and a water-based, pressure-sensitive adhesive, this film is recommended for application to interior and exterior glass or plastic surfaces. It is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same tools and techniques used for installing window tinting films. This film does take on fingerprints but is fully washable and cleans easily with SimGlas Window Film Cleaner and Polish. Installers should work with clean hands when handling this film.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years interior from the date of installation and (1) year for exterior applications. Life expectancy is 3-5 years for exterior applications. See warranty information for specific details. The warranty does not apply to film problems caused by defective application.

THIS PRODUCT IS 100% Manufactured in the USA

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224

www.decorativefilm.com