

## SOLYX® Glass Finishes

### SXEG-4868 Oasis



#### Product Description

SOLYX® SXEG-4868 Oasis is a lovely polyester film with a kaleidoscope-like pattern in light, muted colors. The pattern repeats at 48" horizontally and 21" vertically. This translucent film provides semi-obscured visibility while allowing excellent light transmission.

#### Specifications

|                             |                    |
|-----------------------------|--------------------|
| Product Codes               | SXEG-4868          |
| Product Family              | Stained Glass      |
| Film Type                   | Polyester          |
| Adhesive Type               | Pressure-Sensitive |
| Usage                       | Interior           |
| Available Width(s)          | 48"                |
| Thickness                   | 2 mil              |
| Visible Light Transmission  | 59%                |
| UV Transmission             | 45%                |
| Total Solar Energy Absorbed | Average -35%       |
| U Value                     | Average - 1.75     |
| Shading Coefficient         | Average -.95       |
| Reflectance                 | 0 – 8%%            |
| Total Solar Energy Rejected | Average - 35%      |

#### Product Construction

##### Face Film

2 mil Polyester

##### Adhesive

Clear, Pressure-Sensitive

##### Release Liner

Silicone Coated

#### Product Details

SOLYX® SXEG-4868 Oasis is a lovely polyester film with a kaleidoscope-like pattern in light, muted colors. The pattern repeats at 48" horizontally and 21" vertically. Made from durable polyester and supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive, it is recommended for application to interior and exterior glass (inside surface). This beautiful film is ideal for privacy, decorative, or architectural applications, adding privacy and color to any glass surface.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)