

## SOLYX® Glass Finishes SXJ-0549 Variable Lines Gradient



### Product Details

**SOLYX® SXJ-0549 Variable Lines Gradient** is a lightly textured, frosted polyester film with varying widths and shades of vertical white stripes that gradually fade from the bottom up. This durable film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Product Description

**SOLYX® SXJ-0549 Variable Lines Gradient** is a lightly textured, frosted polyester film with varying widths and shades of vertical white stripes that gradually fade from the bottom up. It is ideal for providing graduated privacy and excellent light transmission.

#### Specifications

|                             |                    |
|-----------------------------|--------------------|
| Product Code                | SXJ-0549           |
| Product Family              | Gradient           |
| Film Type                   | Polyester          |
| Adhesive Type               | Pressure-Sensitive |
| Usage                       | Interior           |
| Available Height            | 71" (or custom)    |
| Full Roll Length            | 95 linear feet     |
| Thickness                   | 4mil               |
| Shading Coefficient         | 0.55               |
| Visible Light Reflection    | 27%                |
| Visible Light Transmission  | Average - 42%      |
| UV Transmission             | 2%                 |
| Total Solar energy Rejected | 38%                |
| Solar Energy Absorbed       | 25%                |
| Infra-Red Transmission      | 70%                |

### Installation and Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

#### Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

4 mil Polyester

#### Adhesive

Clear, Pressure-Sensitive

#### Release Liner

Silicone Coated

### Product Distribution and Contact Information

#### Distribution

**SOLYX®** Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

#### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)