

SOLYX® Glass Finishes

SXJ-0592 Isoline Dual Frost Gradient



Product Description

SOLYX® SXJ-0592 Isoline Dual Frost Gradient is a dual fading gradient of grey frosted horizontal stripes that gradually reduce in thickness from the center band up and down. It is ideal for semi-privacy while still allowing excellent light transmission.

Specifications

Product Code	SXJ-0592
Product Family	Gradient
Film Type	Polyester
Adhesive Type	Removable PS
Usage	Interior
Available Height	60" (or custom)
Full Roll Length	95 linear feet
Thickness	4mil
Shading Coefficient	0.55
Visible Light Reflection	27%
Visible Light Transmission	Average - 23%
UV Transmission	2%
Total Solar energy Rejected	38%
Solar Energy Absorbed	25%
Infra-Red Transmission	70%

Product Construction

Face Film

4mil Polyester

Adhesive

Clear, Removable, Pressure-Sensitive

Release Liner

Silicone Coated

Product Details

SOLYX® SXJ-0592 Isoline Dual Frost Gradient is a dual fading gradient of grey frosted horizontal stripes that gradually reduce in thickness from the center band up and down. The center band measures approximately 22 ½". This durable polyester film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

NOTE: A solid match to this film is SXJ-0597 Isoline Frost.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com