

## SOLYX® Glass Finishes

### SXJ-0595 Dual Strata Gradient



#### Product Description

SOLYX® SXJ-0595 Dual Strata Gradient is a simple frosted, dual fading gradient of blurred and tapering lines from white to clear from the center up and down. This film is ideal for providing semi-privacy while still allowing excellent light transmission.

#### Specifications

|                             |                    |
|-----------------------------|--------------------|
| Product Code                | SXJ-0595           |
| Product Family              | Gradient           |
| Film Type                   | Polyester          |
| Adhesive Type               | Pressure-Sensitive |
| Usage                       | Interior           |
| Available Height            | 60" (or custom)    |
| Full Roll Length            | 98 linear feet     |
| Thickness                   | 2 mil              |
| Shading Coefficient         | 0.55               |
| Visible Light Reflection    | 27%                |
| Visible Light Transmission  | Average - 49%      |
| UV Transmission             | 2%                 |
| Total Solar energy Rejected | 38%                |
| Solar Energy Absorbed       | 25%                |
| Infra-Red Transmission      | 70%                |

#### Product Construction

##### Face Film

2mil Polyester

##### Adhesive

Clear, Pressure-Sensitive

##### Release Liner

Silicone Coated

#### Product Details

SOLYX® SXJ-0595 Dual Strata Gradient is a simple frosted, dual fading gradient of blurred and tapering lines from white to clear from the center up and down. This durable polyester film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)