

## SOLYX® Glass Finishes

### SXJ-0725 Dual Etch Gradient 72"



#### Product Description

**SOLYX® SXJ-0725 Dual Etch Gradient 72"** is a lightly textured etched polyester film with a dual fade. Semi-opaque in the center, it fades to clear up and down. It is ideal for providing graduated privacy and good light transmission.

#### Specifications

|                            |                    |
|----------------------------|--------------------|
| Product Code               | SXJ-0725           |
| Product Family             | Gradient           |
| Film Type                  | Polyester          |
| Adhesive Type              | Pressure-Sensitive |
| Usage                      | Interior           |
| Available Height           | 72"                |
| Full Roll Length           | 98 linear feet     |
| Thickness                  | 2mil               |
| Visible Light Transmission | Average - 80%      |
| UV Transmission            | Average - 72%      |
| Infra-Red Transmission     | Average - 75%      |

#### Product Construction

**Face Film**  
2mil Polyester

**Adhesive**  
Clear, Pressure-Sensitive

**Release Liner**  
Silicone Coated

#### Product Details

**SOLYX® SXJ-0725 Dual Etch Gradient 72"** is a lightly textured etched polyester film with a dual fade which is semi-opaque in the center fading to clear, up and down. This durable film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

**SOLYX®** Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC. Samples submitted upon request.

##### Contact Information

Decorative Films, LLC  
1-888-657-5224  
[www.decorativefilm.com](http://www.decorativefilm.com)