

SOLYX® Glass Finishes

SXR-9829 Glassfrost



Product Description

SOLYX® SXR-9829 Glassfrost is a clear, semi-transparent, fine-textured, polyolefin film. Environmentally friendly, it is ideal for semi-obscuring direct visibility while allowing excellent light transmission.

Specifications

Product Code	SXR-9829
Product Family	Frosted
Film Type	Polyolefin
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	54" (1371mm)
Full Roll Length	100 linear feet (30.5m)
Thickness	3.75 mil
Visible Light Transmission	87%
UV Transmission	83%
Infra-Red Transmission	89%

Product Construction

Face Film

3.75 mil Polyolefin

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Product Details

SOLYX® SXR-9829 Glassfrost film is a clear, semi-transparent, fine-textured film that is environmentally friendly and UL-410 classified for slip resistance. Manufactured from polyolefin, it is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive. This product is recommended for application to interior, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Features

Typical Characteristics

Target Adhesion Values: 15 min. 24hr.

(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel) 65 oz. 75 oz.

Minimum Application Temperature: 50°F

Service Temperature Range: -40°F to +180°F

Shelf Life (@ 73°F, 50% RH): 2 years

Outdoor Durability: Indoor Use Only

Chemical Resistance

Distilled Water (24hr): No Effect

Detergent (24hr): No Effect

10% HC1 (10min): No Effect

10% Ammonium Hydroxide (10min): No Effect

Gasoline (1hr): No Effect

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com