

## SOLYX® Glass Finishes

### SXR-9829 Glassfrost



#### Product Description

SOLYX® SXR-9829 Glassfrost is a clear, semi-transparent, fine-textured, polypropylene film. Environmentally friendly, it is ideal for semi-obscuring direct visibility while allowing excellent light

#### Specifications

Product Code	SXR-9829
Product Family	Frosted
Film Type	Polypropylene
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	54" (1371mm)
Full Roll Length	100 linear feet (30.5m)
Thickness	3.75 mil
Visible Light Transmission	87%
UV Transmission	83%
Infra-Red Transmission	89%

transmission.

#### Product Construction

##### Face Film

3.75 mil Polypropylene

##### Adhesive

Clear, Pressure-Sensitive

##### Release Liner

Silicone Coated

#### Product Details

SOLYX® SXR-9829 Glassfrost film is a clear, semi-transparent, fine-textured film that is environmentally friendly and UL-410 classified for slip resistance. Manufactured from polypropylene, it is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive. This product is recommended for application to interior, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Features

##### Typical Characteristics

Target Adhesion Values: 15 min. 24hr.

(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel) 65 oz. 75 oz.

Minimum Application Temperature: 50°F

Service Temperature Range: -40°F to +180°F

Shelf Life (@ 73°F, 50% RH): 2 years

Outdoor Durability: Indoor Use Only

##### Chemical Resistance

Distilled Water (24hr): No Effect

Detergent (24hr): No Effect

10% HC1 (10min): No Effect

10% Ammonium Hydroxide (10min): No Effect

Gasoline (1hr): No Effect

#### Installation and Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

##### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Distribution and Contact Information

##### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC. Samples submitted upon request.

##### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)