

SOLYX® Glass Finishes SXRR-8000 Creation Stained Glass



Product Details

SOLYX® SXRR-8000-O Creation Stained Glass – Opalescent and **SXRR-8000-T Creation Stained Glass – Transparent** are beautifully colored, attractively designed films in blue and orange hues that provide a stained glass look, available in both opalescent (O) and transparent (T) finishes. These durable polyester films are supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive. They are recommended for application to interior and exterior glass (inside surface) and are ideal for privacy, decorative, or architectural applications, adding beauty and color to any window or glass surface.

Flammability Rating

These products meet ASTM E84 and are classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

These products have zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. These films are applied using the same tools and techniques used for installing window tinting films.

Warranty

These **SOLYX®** products will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SXRR-8000 Creation Stained Glass is a beautifully colored, attractively designed film in blue and orange hues that provides a stained glass look. Available in opalescent (O) and transparent (T) finishes, this film provides good light transmission.

Specifications

Product Code	SXRR-8000-O, SXRR-8000-T
Product Family	Stained Glass
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	48"
Thickness	2-4 mil
Visible Light Transmission	O=37%, T=21%
UV Transmission	O=2% , T=<1%
Total Solar Energy Absorbed	35%
U Value	1.75
Shading Coefficient	.95
Reflectance	0%
Total Solar Energy Rejected	35%

Product Construction

Face Film

2-4 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated