

UltraCool®- S3560



Product Description

UltraCool-3560: SILVER HEAT REJECTION FILM: A Neutral appearance window film with minimum light reduction. Rejects 65% Solar Heat and blocks 99% of the harmful UV rays

Specifications

Product Code	UltraCool-S3560
Product Family	Solar Control
Film Type	Polyester
Adhesive Type	Acrylic Pressure Sensitive
Usage	Interior
Available Width(s)	60"
Full Roll Length	100 linear feet
Thickness	2 mil
Shading Coefficient (%)	.40
Visible Light Reflectance (%)	37%
Visible Light Transmission (%)	31.9%
UV Transmission (%)	1%
Total Solar Energy Absorbed	46.1%
Total Solar Energy rejected (%)	65%

Product Construction

Face Film: 2mil metalized Polyester

Adhesive: Solvent Acrylic Pressure Sensitive

Liner: Transparent Synthetic

Product Detail

UltraCool-S3560 Silver Films are recommended for application to interior glass, exterior glass (inside surface) This film is made of durable transparent Silver metalized Polyester. The adhesive is protected by a synthetic release liner.

Fire Rating

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions. Installed using the same methods for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of Ten (10) years from the date of installation. See Warranty information for specific details.

Product Distribution and Contact Information

Distribution

Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC

Samples submitted upon request.

Contact Information

Contact Decorative Films, LLC at 1-888-657-5224 or www.decorativefilm.com