

# UltraCool®-s20-osw Outside Weatherable



**UltraCool-S20-OSW** UltraCool exterior silver reflective window films set the industry standard as one of the most powerful and economical solar heat rejecting films providing maximum heat rejection by being the first line of defense against solar heat and glare.

**Key Benefits**

Filming the exterior maximizes heat rejection with up to 82% Total Solar Energy Rejected. The film has an exterior grade scratch resistant coating!  
 Provides a refreshed and uniform look to dated buildings.  
 Maximum heat rejection means maximum saving on air conditioning costs. UV blockers protect people and property from damaging UV rays.

**Fire Rating**

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

**Product Description**

**UltraCool-S20-OSW: SILVER HEAT REJECTION FILM:**

Outside Weatherable Heat Rejection Film is engineered for exterior applications.

**Specifications**

Product Code	UltraCool-S20-OSW
Product Family	Solar Control
Film Type	Polyester
Adhesive Type	Acrylic Pressure Sensitive
Usage	EXTERIOR
Available Width(s)	60", 72"
Full Roll Length	100 linear feet
Thickness	4 mil
Shading Coefficient (%)	.22
Visible Light Reflectance (%)	61%
Visible Light Transmission (%)	16%
UV Transmission (%)	1%
Total Solar Energy Absorbed	25%
<b>Total Solar Energy rejected (%)</b>	<b>82%</b>
Glare Reduction	82%

**Product Construction**

**Face Film:** 4mil metalized Outside Weatherable Polyester

**Adhesive:** Solvent Acrylic Pressure Sensitive

**Liner:** Transparent Synthetic

**Installation and Warranty**

**Installation**

Installation should be in accordance with manufacturer's installation instructions. Installed using the same methods for installing window films. Exterior installations require a thin bead of edge sealant around the edges after installation.

**Approved Sealants:**

GE SCS2000 SilPruf, Dow Corning 995, GE Silicone II1  
 Dow Corning 7951, Dow Corning 7901, Tremsil® 6001  
 DuraSil™1

**Warranty**

This product will be free from defects in material and manufacture for a period of Ten (10) years from the date of installation. See Warranty information for specific details.

**Product Distribution and Contact Information**

**Distribution**

**Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC

Samples submitted upon request.

**Contact Information**

Contact Decorative Films, LLC at 1-888-657-5224 or [www.decorativefilm.com](http://www.decorativefilm.com)

**Product Detail**