

SOLYX® Glass Finishes

UltraCool®- S6060 60% VLT Silver Window Film



Product Description

SOLYX® UltraCool-S6060 60% VLT Silver Window Film is a neutral appearance window film that rejects 43% of solar heat and blocks 99% of harmful UV rays while allowing excellent light transmission.

Specifications

Product Code	UltraCool-S6060
Product Family	Solar Control
Film Type	Polyester
Adhesive Type	Acrylic, Pressure-Sensitive
Usage	Interior
Available Width(s)	60"
Full Roll Length	100 linear feet
Thickness	2 mil
Shading Coefficient	.66
Visible Light Reflectance	13.6%
Visible Light Transmission	68%
UV Transmission	<1%
Total Solar Energy Absorbed	28%
Total Solar Energy Rejected	43%

Product Construction

Face Film: 2 mil Metalized Polyester

Adhesive: Solvent Acrylic, Pressure-Sensitive

Liner: Transparent Synthetic

Product Details

SOLYX® UltraCool-S6060 60% VLT Silver Window Film is a neutral appearance window film that rejects 43% of solar heat and blocks 99% of harmful UV rays while allowing excellent light transmission. Recommended for application to interior glass and exterior glass (inside surface), this film is made of durable, transparent, silver metalized polyester and is supplied with an adhesive that is protected by a synthetic release liner. It is ideal for providing daytime privacy and rejecting heat.

Flammability Rating

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are manufactured by Decorative Films LLC and are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com